OSM/TR-82/2

Surface Mining Water Diversion Design Manual

September 1982

United States Department Of The Interior

Office Of Surface Mining

Technical Services & Research

OSM/TR-82/2

Surface Mining Water Diversion Design Manual

September 1982

Prepared For:

U.S. Department Of The Interior

Office Of Surface Mining

Contract No. J5101050

By: Simons, Li & Associates, Inc.
P.O. Box 1816
Fort Collins, Colorado 80522

United States Department Of The Interior

Office Of Surface Mining

Technical Services & Research

CONTRIBUTORS

D. B. Simons, Principal Engineer

R. M. Li, Principal Hydraulic Engineer

J. D. Schall, Senior Hydraulic Engineer

M. R. Peterson, Hydraulic Engineer

B. A. Anderson, Hydraulic Engineer

R. M. Summer, Geomorphologist

W. T. Fullerton, Senior Hydraulic Engineer

For sale by the Superintendent of Documents, U.S. Government Printing Office Washington, D.C. 20402

TABLE OF CONTENTS

PART 1: DESIGN PROCEDURES FOR CONDITIONS TYPICAL OF THE EASTERN COAL PROVINCE

Page

LIST OF FIGURES xiii
LIST OF TABLES xix
ACKNOWLEDGEMENTS xxi
CONVERSION FACTORS xxiii

I. INTRODUCTION

1.1 The Problem 1.1
1.2 Control of Drainage on a Mine Site 1.2
1.3 OSM Regulations Concerning Water Diversions 1.3
1.4 Applications of Water Diversion Structures 1.4
1.5 Problems Unique to OSM Regions I and II (Eastern Coal Province) 1.13

1.5.1 Geographic Considerations 1.13
1.5.2 Specific Problems Observed in OSM Regions I and II (Eastern Coal Province) 1.16

1.6 Design Manual Organization and Use 1.21

1.6.1 Design Manual Organization 1.21
1.6.2 Design Manual Use 1.25

1.7 References 1.27

II. BASIC INFORMATION REQUIRED FOR DIVERSION DESIGN 2.1

III. HYDROLOGIC ANALYSIS

3.1 Introduction 3.1
3.2 Rational Method 3.3
3.3 SCS TP-149 Method 3.10
3.4 Calculation Procedures 3.11

3.4.1 Rational Formula 3.11
3.4.2 SCS TP-149 Method 3.15

3.5 Example Using Step-By-Step Procedures Outlined Above . . 3.15

3.5.1 Rational Formula 3.15
3.5.2 SCS TP-149 Method 3.16

3.6 References 3.17

TABLE OF CONTENTS (continued)

Page

IV. BASIC CONCEPTS OF OPEN-CHANNEL FLOW

4.1 Introduction 4.1
4.2 Parameters Describing the Hydraulics of Open-Channel Flow 4.1

4.2.1 General 4.1
4.2.2 Variables Describing the Boundary Geometry . . . 4.1
4.2.3 Variables Describing the Flow 4.2
4.2.4 Variables Describing the Fluid 4.4
4.2.5 Parameters Describing Open-Channel Flow 4.4
4.2.6 Parameters Describing Boundary Roughness Conditions 4.5

4.3 Governing Equations 4.5
4.4 Steady and Uniform Flow Formulas for Open Channels - The Manning Equation 4.8
4.5 Resistance to Flow 4.9
4.6 Selection of Channel Cross Section 4.10
4.7 Variances in Flow Conditions 4.13

4.7.1 Superelevation 4.13
4.7.2 Freeboard 4.18

4.8 Example 4.19
4.9 References 4.22

V. STEEP SLOPE CHANNEL DESIGN

5.1 Introduction 5.1
5.2 General Riprap Considerations 5.2

5.2.1 Definition of Riprap 5.2
5.2.2 Types of Riprap 5.2
5.2.3 General Considerations 5.3
5.2.4 Properties of Rock Used as Riprap 5.4
5.2.5 Riprap Gradation and Placement 5.4
5.2.6 Riprap Thickness 5.8
5.2.7 Filter Layers 5.8

5.2.7.1 Granular Filters 5.9
5.2.7.2 Plastic Filter Cloths 5.13

5.3 Steep Channel Riprap Design 5.14

5.3.1 Introduction 5.14
5.3.2 Simplified Design Procedures 5.15

TABLE OF CONTENTS (continued)

Page

5.4 Channel Entrances and Exits 5.22
5.5 Design Procedures Summary 5.22

5.5.1 Criteria for Riprap Design 5.22

5.6 Design Examples - Using Step-By-Step Procedures Outlined Above 5.23

5.6.1 Design Example for Steep Slope Protection . . . 5.23
5.6.2 Design Example for Granular Filter Layer 5.24
5.6.3 Plastic Filter Cloth Design Example 5.28
5.6.4 Entrance and Exit Design Example 5.29

5.7 References 5.31

VI. MILD SLOPE CHANNEL DESIGN

6.1 Introduction 6.1
6.2 Determination of Drainage Patterns and Diversion Alignment 6.3
6.3 Alluvial Channel Concepts 6.5

6.3.1 General Sediment Transport Theory 6.5
6.3.2 Stream Form and Classification 6.7

6.3.2.1 Straight Channels 6.7
6.3.2.2 The Braided Stream 6.9
6.3.2.3 The Meandering Channel 6.9

6.3.3 Bed and Bank Material 6.10
6.3.4 Lane Relation 6.12
6.3.5 Shields' Relation 6.14
6.3.6 Sediment Transport Equations 6.15

6.4 Stable Alluvial Channel Design - Method of Maximum Permissible Velocity 6.18

6.4.1 General Procedure 6.18
6.4.2 Evaluating the Channel for Reasonable Shape . . 6.23
6.4.3 Evaluation of the Need for Rock Riprap or Grade Control Structures 6.24

6.5 Vegetative Linings 6.25

6.5.1 General 6.25
6.5.2 Design Procedure - Maximum Permissible Velocity 6.25
6.5.3 Composite Linings 6.33
6.5.4 Establishing Vegetative Linings 6.35

TABLE OF CONTENTS (continued)

Page

6.6 Rock Riprap Design 6.37

6.6.1 General 6.37
6.6.2 Recommended Riprap Design Procedure 6.38
6.6.3 Riprap Protection in Channel Bends 6.38

6.7 Riprap Design with Grade Control Structures 6.38

6.7.1 Application 6.38
6.7.2 Types of Grade Control Structures 6.43
6.7.3 Design Procedure Involving Grade Control Structures 6.43
6.7.4 Spacing of Grade Control Structures 6.45
6.7.5 Protection of Grade Control Structures 6.52

6.8 Design Procedure Summary 6.52
6.9 Design Examples - Using Step-By-Step Procedures Outlined Above 6.55

6.9.1 Example of the Lane Relation Evaluation of Disturbances to Alluvial Channels 6.55
6.9.2 Example of the Method of Maximum Permissible Velocity (Alluvial or Bedrock Channel) 6.56
6.9.3 Example of Vegetated Channel Design 6.58
6.9.4 Example of Riprap Desing 6.59
6.9.5 Grade Control Structures 6.61

6.10 References 6.63

VII. TRANSITION DESIGN

7.1 Basic Considerations 7.1
7.2 General Design Principles 7.2
7.3 Simplified Design Procedure 7.3
7.4 Transition Protection 7.4
7.5 Special Considerations 7.5
7.6 Channel Junctions 7.5
7.7 Example of Transition Design 7.7
7.8 References 7.10

VIII. ROCK DURABILITY AND SLOPE STABILITY EVALUATIONS

8.1 Introduction 8.1
8.2 Rock Durability Evaluation 8.1

8.2.1 Purpose and Scope 8.1
8.2.2 General Considerations of Test Procedure 8.2
8.2.3 Site Investigations 8.2

TABLE OF CONTENTS (continued)

			Page
		8.2.3.1 General	8.2
		8.2.3.2 Landform Characteristics	8.4
		8.2.3.3 Rock Type	8.4
		8.2.3.4 Rock Mass Conditions	8.4
		8.2.3.5 Performance	8.5
	8.2.4	Field Testing	8.6
	8.2.5	Laboratory Testing	8.7
		8.2.5.1 General	8.7
		8.2.5.2 Los Angeles Abrasion Test	8.8
		8.2.5.3 Point Load Test	8.8
		8.2.5.4 Schmidt Hammer	8.8
		8.2.5.5 Freeze-Thaw Testing	8.9
		8.2.5.6 Sulfate Soundness Test	8.9
		8.2.5.7 Slake Durability	8.9
	8.2.6	Application of Procedure	8.10
		8.2.6.1 General Inspection	8.10
		8.2.6.2 Durability Flow Chart Evaluation	8.10
	8.2.7	Summary and Conclusions	8.18
8.3	Geotechnical Stability Considerations		8.20
	8.3.1	Introduction	8.20
	8.3.2	Slope Stability Factors	8.20
		8.3.2.1 Natural Ground Surface Slope	8.21
		8.3.2.2 Earth Material Type	8.21
		8.3.2.3 Ground Water	8.21
		8.3.2.4 Design Flow	8.27
		8.3.2.5 Other Stability Factors	8.27
	8.3.3	Stability Problems Unique to the Appalachian Basin	8.27
		8.3.3.1 Shale	8.27
		8.3.3.2 Sandstone	8.28
		8.3.3.3 Colluvial Deposits	8.28
		8.3.3.4 Aquifers and Underclays	8.28
		8.3.3.5 Existing Landslides	8.28
8.4	References		8.31

TABLE OF CONTENTS (continued)

Page

IX. ECOLOGICAL CONSIDERATIONS

9.1 General 9.1
9.2 Water Quality 9.1
9.3 Physical Characteristics 9.2
9.4 Stream Study and Investigation Procedures 9.4
9.5 Reconstruction 9.5
9.6 Conclusion 9.8
9.7 References 9.10

X. COMPREHENSIVE DESIGN EXAMPLE

10.1 General Description 10.1
10.2 Hydrologic Design 10.1

10.2.1 Rational Formula 10.1
10.2.2 SCS TP-149 Method 10.4

10.3 Diversion Channel Designs 10.4

10.3.1 Channel A 10.4
10.3.2 Diversion Channel B 10.16
10.3.3 Diversion Channel C 10.20
10.3.4 Diversion Channel D 10.25

10.4 Transition Design 10.29

10.4.1 Channels A and B 10.29
10.4.2 Channels C and D 10.29

TABLE OF CONTENTS (continued)

PART 2: ADDITIONAL DESIGN PROCEDURES FOR CONDITIONS TYPICAL OF WESTERN COAL REGIONS

Page

XI. INTRODUCTION

11.1 Purpose of Part 2 . . . . . 11.1
11.2 Special Problems of Sandy Soils 11.1

11.2.1 Sediment Yield 11.1
11.2.2 Stream Response 11.2
11.2.3 Stable Channel Design 11.2

11.3 Organization 11.3

XII. OPEN CHANNEL FLOW CONCEPTS FOR SANDY SOIL DIVERSIONS

12.1 Introduction 12.1
12.2 Selection of Channel Shape 12.1
12.3 Normal Depth Calculation 12.1
12.4 Resistance to Flow 12.1

12.4.1 Bed Configuration, Flow Phenomena, and Resistance to Flow 12.3

12.4.1.1 Plane Bed Without Sediment Movement . 12.3
12.4.1.2 Ripples 12.3
12.4.1.3 Dunes 12.5
12.4.1.4 Plane Bed With Sediment Movement . . . 12.5
12.4.1.5 Antidunes 12.5
12.4.1.6 Chutes and Pools 12.6

12.4.2 Regime of Flow in Alluvial Channels 12.6

12.4.2.1 Lower Flow Regimes 12.7
12.4.2.2 Upper Flow Regimes 12.7
12.4.2.3 Transitions 12.7

12.4.3 Recommended Values of Manning's n 12.9

12.5 Additional Depth Components Due to Bed Forms 12.9
12.6 Superelevation 12.9
12.7 Freeboard for Sand Bed Channels 12.9
12.8 Evaluation of Channel for Reasonable Shape 12.11
12.9 Examples 12.12

12.9.1 Iterative Solution of the Manning Equation . . . 12.12
12.9.2 Evaluation of Bed Form and Manning n Assumption 12.12
12.9.3 Evaluation of Superelevation and Freeboard . . . 12.13

12.10 References 12.16

TABLE OF CONTENTS (continued)

Page

XIII. SANDY SOIL ALLUVIAL CHANNEL CONCEPTS

13.1 General Sediment Transport Concepts 13.1
13.2 Bed Material 13.2
13.3 Bank Material 13.3

13.3.1 Seepage Forces 13.4
13.3.2 Piping 13.4
13.3.3 Mass Wasting 13.4

13.4 Lane's Relation 13.5
13.5 Stream Form and Classification 13.5
13.6 Slope-Discharge Relation 13.5
13.7 Sediment Transport Equations 13.7
13.8 Design Procedure 13.9
13.9 Design Example 13.15
13.10 References 13.16

XIV. BASIC DESIGN PROCEDURES FOR SANDY SOIL CHANNELS

14.1 Introduction 14.1
14.2 Dynamic Equilibrium Concept 14.2
14.3 Equilibrium Slope 14.2
14.4 Equilibrium Slope Design Procedure 14.3
14.5 Evaluation of the Need for Rock Riprap or Drop Structures 14.4
14.6 Design Example 14.5

XV. DESIGN OF RIPRAP LININGS IN SANDY SOILS

15.1 Introduction 15.1
15.2 General Considerations 15.1
15.3 Channel Roughness Coefficient 15.3
15.4 Design Procedures Summary 15.5

15.4.1 Criteria for Riprap Design 15.5
15.4.2 Design Procedure for Riprap Lined Channel Bends 15.9

15.5 Design Examples 15.10

15.5.1 Riprap Design Example - Use Step by Step Procedure in Section 15.5.1 . . . . . 15.10
15.5.2 Design Example for Granular Filter Layer 15.14
15.5.3 Plastic Filter Cloth Design Example 15.18
15.5.4 Design Example for Riprap Bend Protection . . . 15.18

15.6 References 15.20

TABLE OF CONTENTS (continued)

Page

XVI. DESIGN OF DROP STRUCTURES

16.1 Site Selection 16.1
16.2 Type of Structure 16.1
16.3 Height, Number and Spacing of Structures 16.1
16.4 Local Scour 16.2
16.5 Design of Rock Riprap Drop Structures 16.2
16.6 Summary of the Design Procedure for Drop Structures . . . 16.3
16.7 Design Example 16.5

XVII. TRANSITION DESIGN

17.1 Basic Considerations 17.1
17.2 Design of Dikes 17.1

17.2.1 Length 17.1
17.2.2 Height 17.3
17.2.3 Width 17.3
17.2.4 Sideslope 17.3
17.2.5 Protection 17.3

17.3 Design Examples 17.5

17.3.1 Example of Transition Design 17.5
17.3.2 Example of Dike Design 17.7

XVIII. ROCK DURABILITY CONSIDERATIONS FOR WESTERN COAL REGIONS

18.1 General 18.1
18.2 Additional Considerations Applicable to Western Coal Regions 18.1
18.3 Summary 18.2
18.4 References 18.5

XIX. COMPREHENSIVE EXAMPLE

19.1 Design of Diversion Channel Using Equilibrium Slope Concept 19.1
19.2 Design of Channel Lining 19.6
19.3 Design of Drop Structures (Using Step-by-Step Procedure Given in Section 16.6) 19.16
19.4 Design of Channel Inlet 19.24
19.5 Design of Channel Outlet 19.33

XX. RESEARCH NEEDS 20.1

TABLE OF CONTENTS (continued

APPENDIX A - U.S. WEATHER BUREAU TECHNICAL PAPER 40 CHARTS

APPENDIX B - SCS TP-149 DESIGN CHARTS

APPENDIX C - DESIGN CHARTS FOR SOLVING THE MANNING EQUATION AND VALUES FOR THE MANNING n

APPENDIX D - DEVELOPMENT OF THE DESIGN EQUATIONS FOR STATIC EQUILIBRIUM SLOPE COMPUTATIONS

APPENDIX E - BIOLOGICAL STREAM INVESTIGATION PROCEDURES

LIST OF FIGURES

		Page
Figure 1.1.	Drainage in countour mining	1.7
Figure 1.2.	Relocated channel in area mining	1.8
Figure 1.3.	Drainage patterns in the mountain removal method	1.9
Figure 1.4.	Design requirements for valley fills	1.10
Figure 1.5	Plan view of contour mining drainage plan	1.14
Figure 1.6	Plan view of a contour mine drainage plan	1.15
Figure 1.7	Flow chart illustrating design manual organization	1.26
Figure 3.1.	Nomograph for computing t_c (from West Virginia Department of Highways)	3.6
Figure 3.2.	Time of concentration of small rural drainage basins (from West Virginia Department of Highways)	3.7
Figure 3.3.	Conversion factors for durations less than one hour	3.8
Figure 4.1.	Definition sketch of the energy and hydraulic grade lines in open-channel flow	4.7
Figure 4.2	Relationship between side slope value, z and slope angle, Θ	4.14
Figure 4.3	Angle of repose	4.16
Figure 4.4.	Definition sketch of superelevation in a channel bend	4.17
Figure 5.1	Definition sketch illustrating steep and mild slope riprap gradation based on recommended guidelines	5.7
Figure 5.2	Gradation curves for three-inch diameter blast holes in hard shale and sandstone (U.S. Army Engineer Waterways Experiment Station, 1975)	5.11
Figure 5.3	Steep slope riprap design, trapezoidal channels, 2:1 sideslopes	5.16
Figure 5.4.	Steep slope riprap design, trapezoidal channels, 2:1 sideslopes, 6 ft base width	5.17

LIST OF FIGURES (continued)

		Page
Figure 5.5.	Steep slope riprap design, trapezoidal channels, 2:1 sideslopes, 10 ft base width	5.18
Figure 5.6.	Steep slope riprap design, trapezoidal channels, 2:1 sideslopes, 14 ft base width	5.19
Figure 5.7.	Steep slope riprap design, trapezoidal channels, 2:1 sideslopes, 20 ft base width	5.20
Figure 5.8.	Final channel dimensions	5.25
Figure 5.9.	Gradations of filter blanket for design example	5.26
Figure 5.10.	Entrance and exit protection on steep conveyance channel	5.30
Figure 6.1.	Watershed-river system	6.6
Figure 6.2.	River channel patterns	6.8
Figure 6.3.	Schematic of the Lane relationship for qualitative analysis	6.13
Figure 6.4.	Shields' Diagram	6.16
Figure 6.5a.	Solution of the Manning equation for retardance A (very high vegetal retardance). (U.S. SCS)	6.28
Figure 6.5b.	Solution of the Manning equation for retardance B (high vegetal retardance). (U.S. SCS)	6.29
Figure 6.5c.	Solution of the Manning equation for retardance C (moderate vegetal retardance). (U.S. SCS)	6.30
Figure 6.5d.	Solution of the Manning equation for retardance D (low vegetal retardance). (U.S. SCS)	6.31
Figure 6.5e.	Solution of the Manning equation for retardance B (very low vegetal retardance). (U.S. SCS)	6.32
Figure 6.6.	Dimensions and velocity distribution, Ree (1951)	6.34
Figure 6.7.	Detail of suggested grass to concrete junction	6.36
Figure 6.8.	Effect of bend on boundary shear stress (after Soil Conservation Service design manual)	6.41

LIST OF FIGURES (continued)

		Page
Figure 6.9.	Definition sketch of a rock riprap drop structure (protection upstream and downstream according to Section 5.4)	6.44
Figure 6.10a.	Relationship between hydraulic radius R and K for trapezoidal channel with 2:1 side slopes and 6-foot base width	6.46
Figure 6.10b.	Relationship between hydraulic radius R and K for trapezoidal channel with 2:1 side slopes and 10-foot base width	6.48
Figure 6.10c.	Relationship between hydraulic radius R and K for trapezoidal channel with 2:1 side slopes and 14-foot base width	6.50
Figure 7.1.	Recommended junction angle between a major diversion and a natural stream channel	7.6
Figure 7.2	Converging transition design example	7.9
Figure 8.1	Rock durability flow chart: Procedure for evaluating rock suitable as riprap and channel lining. Part I - Site investigation; Part II - Laboratory investigation	8.3
Figure 8.2a.	Rock durability field flow chart	8.12
Figure 8.2b.	Rock durability laboratory flow chart	8.15
Figure 8.3.	Stratigraphic description of overburden at a mine site in eastern Kentucky	8.16
Figure 8.4.	Rock durability field flow chart: example	8.17
Figure 8.5.	Rock durability field flow chart: example	8.19
Figure 8.6.	Horizontal and vertical extent of cuts for base width of 10 feet (D'appolonia, Inc.)	8.22
Figure 8.7.	Unfavorable orientation of bedding planes (D'appolonia, Inc.)	8.23
Figure 8.8.	Favorable orientation of bedding planes (D'appolonia, Inc.)	8.24
Figure 8.9.	Schematic topographic diagrams of five landforms that are highly susceptible to landslides	8.29

LIST OF FIGURES (continued)

		Page
Figure 9.1.	Channel segment with pond, riffle, pool layout (from Soil Conservation Service, 1977)	9.7
Figure 9.2.	Fish habitat development (from Soil Conservation Service, 1977)	9.9
Figure 10.1.	Topographic map of the design example	10.2
Figure 10.2.	Longitudinal profile of diversion channel A	10.6
Figure 10.3.	Particle size characteristic for diversion channel A from stations 0+00 to 7+80	10.9
Figure 10.4.	Diversion channel A dimensions from station 0+00 to 7+80	10.12
Figure 10.5.	Particle size characteristics for diversion channel A stations 7+80 to 15+80	10.14
Figure 10.6.	Diversion channel A dimensions from stations 7+80 to 15+80	10.17
Figure 10.7.	Longitudinal profile for diversion channel B	10.18
Figure 10.8.	Longitudinal profile for diversion channel C	10.21
Figure 10.9.	Particle size characteristics for diversion channel C	10.23
Figure 10.10.	Diversion channel C dimensions	10.26
Figure 10.11.	Longitudinal profile of diversion channel D	10.27
Figure 10.12.	Diversion channel D dimensions	10.28
Figure 12.1.	Forms of bed roughness in sand channels	12.4
Figure 12.2.	Relation of bed forms to stream power and median fall diameter of bed sediment (after Simons and Richardson, 1966)	12.8
Figure 12.3.	Channel design for straight reach	12.15
Figure 13.1.	Stream and river channel patterns	13.6
Figure 13.2.	Slope-discharge relation for braiding or meandering in sand-bed streams (after Lane, 1957)	13.8

LIST OF FIGURES (continued)

		Page
Figure 13.3.	Values for sediment transport rate based on power relationships	13.10
Figure 13.4.	Values for sediment transport rate based on power relationships	13.11
Figure 13.5.	Values for sediment transport rate based on power relationships	13.12
Figure 13.6.	Values for sediment transport rate based on power relationships	13.13
Figure 13.7.	Values for sediment transport rate based on power relationships	13.14
Figure 14.1.	Physical layout of design example	14.6
Figure 15.1.	Bank protection with rock riprap	15.2
Figure 15.2.	Subareas for determination of an equivalent roughness coefficient	15.4
Figure 15.3.	Graph for determining n_e, six-foot base width	15.6
Figure 15.4.	Graph for determining n_e, ten-foot base width	15.7
Figure 15.5.	Graph for determining n_e, 14-foot base width	15.8
Figure 15.6.	Cross section of diversion channel	15.15
Figure 15.7.	Particle size distribution for base material, riprap and filter layer	15.16
Figure 16.1.	Drop structure design	16.4
Figure 16.2.	Design of drop structure	16.7
Figure 16.3.	Drop structure design cross-sectonal view	16.8
Figure 17.1.	Relationship between dike length, projection angle and meander width	17.2
Figure 17.2.	Schematic diagram of dike cross section	17.4
Figure 17.3.	Transition design	17.6

LIST OF FIGURES (continued)

		Page
Figure 17.4.	Scale drawing of meander width and dike length	17.8
Figure 17.5.	Cross-sectional view of dike	17.10
Figure 19.1.	Schematic diagram of proposed mining operation	19.2
Figure 19.2.	Physical layout of comprehensive example	19.3
Figure 19.3.	Riprap, base material, and filter layer characteristics	19.10
Figure 19.4.	Representative cross section of diversion channel	19.15
Figure 19.5.	Profile view of proposed diversion channel	19.17
Figure 19.6.	Size distribution of base material, riprap, and first filter layer for drop structure	19.19
Figure 19.7.	Size distribution of second filter layer for drop structure	19.23
Figure 19.8.	Profile view of drop structure	19.25
Figure 19.9.	Cross section of drop structure	19.26
Figure 19.10.	Schematic diagram of channel inlet	19.27
Figure 19.11.	Transition design for channel inlet	19.29
Figure 19.12.	Transition design for channel inlet	19.30
Figure 19.13.	Cross-sectional view of dike for channel inlet	19.34
Figure 19.14.	Cross section of North Battle Creek at point of intersection with diversion channel	19.35
Figure 19.15.	Plan view of channel junction	19.37

LIST OF TABLES

		Page
Table 1.1.	Design Requirements by Technologies	1.5
Table 2.1.	Possible Data Required for Diversion Design	2.3
Table 3.1.	Hydrologic Recurrence Interval and Design Event	3.2
Table 3.2.	Time of Concentration for Small Watersheds	3.5
Table 3.3.	Rational Runoff Coefficients (after Schwab et al., 1971)	3.9
Table 3.4.	Runoff Curve Numbers for Hydrologic Soil-Cover Complexes	3.12
Table 3.5.	Soil Conservation Service Soil Group Classifications	3.13
Table 3.6.	Slope Factors for Peak Discharge Computations in the TP-149 Method	3.14
Table 4.1.	Elements of Channel Sections (from Soil Conservation Service, 1954)	4.3
Table 4.2.	Manning's Coefficients of Channel Roughness	4.11
Table 4.3.	Suggested Sideslope z Values	4.15
Table 4.4.	Freeboard Coefficients	4.20
Table 5.1.	Recommended Riprap Gradation Limits	5.6
Table 5.2.	Design D_{50} Values	5.21
Table 6.1a.	Maximum Permissible Velocities Tables by Fortier and Scobey (1926)	6.19
Table 6.1b.	Maximum Permissible Velocities Tables by Etcheverry (1916)	6.20
Table 6.1c.	Maximum Permissible Velocities Tables by U.S. Army Office (1970)	6.21
Table 6.1d.	Formulas for Maximum Permissible Velocity for Canals Constructed in Alluvium	6.22

LIST OF TABLES (continued)

Page

Table 6.2. Permissible Velocities for Channels Lined with Vegetation 6.26

Table 6.3. Guide to Selection of Vegetal Retardance 6.27

Table 6.4. Riprap Requirements for Channel Linings in Mild Slope Channels ($F_r < 0.8$) 6.39

Table 6.5. Classification and Gradation of Ordinary Riprap for Mild Slope Channels ($F_r < 0.8$) 6.40

Table 6.6. Application Conditions for Various Types of Channel Lining 6.53

Table 8.1. Stable Side Slopes for Channels Built in Various Kinds of Materials (from Chow, 1959) 8.25

Table 8.2. General Guidelines for Cut Sections Through Rock 8.26

Table 10.1. Recommended Design Discharges 10.5

Table 12.1. Angles of Repose for Sand Classification 12.2

Table 12.2. Values of Manning's Coefficient n for Design of Channels with Fine to Medium Sand Beds 12.10

Table 18.1. Classes of Rock Weathering 18.3

Table 19.1. Design Depth of Diversion Channel 19.14

ACKNOWLEDGEMENTS

This manual was prepared for the Office of Surface Mining by Simons, Li & Associates, Inc. under contract No. J5101050. The contract was initiated September, 1980, with Mr. Robert Carpenter as the Contracting Officer and Mr. Jonathan Ventura, OSM Region I, as the Technical Project Officer. The cooperation of Mr. Carpenter and the guidance and direction given to the project by Mr. Ventura are greatly appreciated. Additionally, Mr. Ventura made arrangements during the early stages of the project to visit several mine sites. Access to the mine sites and the time and effort spent by OSM field inspectors and mining company personnel significantly contributed to the project. Finally, the contribution to the geotechnical section of the report by project specialist Dr. Robert Johnson, Colorado State University, and the efforts of the Simons, Li & Associates, Inc. administrative, clerical and drafting staff in producing the Design Manual in its final form are greatly appreciated.

This report is based upon work supported by the Office of Surface Mining, Department of the Interior, under Grant No. J5101050.

Any opinions, findings, and conclusions or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the views of the Office of Surface Mining, Department of the Interior.

Conversion Factors: English to International System (SI)*

Unit and Symbol	Multipliers	Unit and Symbol
Inches (in)	25.40	Millimeters (mm)
Inches (in)	2.540	Centimeters (cm)
Inches (in)	0.0254	Meters (m)
Feet (ft)	0.305	Meters (m)
Miles (mi)	1.61	Kilometers (km)
Yards (yd)	0.91	Meters (m)
Square inches (in^2)	6.45	Square centimeters (cm^2)
Square feet (ft^2)	0.093	Square meters (m^2)
Square yards (yd^2)	0.836	Square meters (m^2)
Acres (a)	4,047	Square meters (m^2)
Acres (a)	0.04047	Hectares (ha)
Square miles (mi^2)	2.59	Square kilometers (km^2)
Pint (pt)	0.4732	Liters (l)
Gallon (gal)	3.785	Liters (l)
Cubic feet (ft^3)	0.0283	Cubic meters (m^3)
Acre-feet (a-ft)	1,233	Cubic meters (m^3)
Cubic inches (in^3)	16.4	Cubic centimeters (cm^3)
Cubic feet (ft^3)	0.028	Cubic meters (m^3)
Cubic yards (yd^3)	0.765	Cubic meters (m^3)
Ounce (oz)	28.35	Grams (g)
Pounds (lb)	0.4536	Kilograms (kg)
Tons (short (ts)	907.2	Kilograms (kg)
Tons (short) (ts)	0.9072	Metric tons (tm)
Pounds per square foot (lb/ft^2)	47.9	Newtons per square meter (N/m^2)
Pounds per square inch (lb/in^2)	6.9	Kilonewtons per square meter (kN/m^2)
Gallons (gal)	3.8	Liter (l)
Acre-feet (a-ft)	1,233	Cubic meters (m^3)
Gallons per minute (gal/min)	0.004	Cubic meters per minute (m^3/min)
Miles per hour (mi/h)	0.447	Meters per second (m/s)
Feet per second (ft/s)	0.3048	Meters per second (m/s)
Pounds per square foot (lb/ft^2)	0.4885	Grams per square centimeter (g/cm^2)
Tons (short) per square foot (ts/ft^2)	0.9765	Kilograms per square centimeter (kg/cm^2)
Tons (short) per acre (ts/a)	0.2241	Kilograms per square meter (kg/m^2)
Tons (short) per square mile (ts/mi^2)	350.2	Kilograms per square kilometer (kg/km^2)
Pounds per cubic foot (lbs/ft^3)	16.02	Kilograms per cubic meter (kg/m^3)
Cubic feet per second (ft^3/s)	0.0283	Cubic meters per second (m^3/s)
Cubic feet per second for one day (ft^3/s-d)	2,446	Cubic meters (m^3)

English Conversion Factors for Water Hydrology

Unit and Symbol	Multipliers	Unit and Symbol
Inches per hour (in/h) --------	1.008	Cubic feet per second (ft^3/s)
Inches per hour (in/h) --------	645.3	Cubic feet per second per square mile ($ft^3/s/mi^2$)
Surface inches (in) ----------	0.0833	Acre-feet (a-ft)
Surface inches (in) ----------	645.3	Cubic feet per second per hour ($ft^3/s/h$)
Surface inches (in) ----------	26.89	Cubic feet per second per day ($ft^3/s/d$)
Square miles (mi^2) ----------	640	Acres (a)
Acres (a) ----------	43,560	Square feet (ft^2)
Square feet (ft^2) ----------	144	Square inches (in^2)
Cubic feet per second-days (ft^3/s-d)	1.983	Acre-feet (a-ft)
Miles per hour (mi/h) ---------	1.467	Feet per second (ft/s)

*Example: To convert from inches to millimeters multiply by 25.40.